

PRODUCT SPECIFICATION

HVU-A

Filtration Unit Model A: High Volume,
Small Footprint

PRODUCT DESCRIPTION

BlueFin Model A filtration units are designed for high volume flushing and testing of production, vessels, tanks and large piping systems.

Using Pall corporation NXA Absolute filters, BlueFin can provide filtration to customer specified NAS 1638, SAE 4059F or ISO 4406 classification.

BlueFin Model A filtration units are equipped with a two inch, 125 psi Wilden pneumatic pump there is a separate close recirculation loop for bulk filtration of fluids along with a sample port.

BENEFITS & APPLICATIONS

- Separate close recirculation loop for bulk filtration.
- Units are in a self-contained enclosed skid suitable for offshore and set up for easy transportation.
- One sample port.

GENERAL SPECIFICATIONS

Gallons Per Minute	125
--------------------	-----

Max Pressure Rating	125 psi
---------------------	---------

Pad Eye Specs	GoM Lifting Specs
---------------	-------------------

Weight	900 lbs
--------	---------

Dimensions	5.5'H x 6'L x 3'W
------------	-------------------

PUMP SPECS

2" Wilden Pneumatic Pump

FILTRATION SPECS

NXA1 Bag filters

BlueFin
A **GATE** Energy Company

© 2021 BlueFin. All rights reserved. Sales of BlueFin products and services will be in accord solely with the terms and conditions contained in the contract between BlueFin and the customer.

www.bluefin.energy