

## PRODUCT SPECIFICATION

# MASY-5K

5K Manifold Assembly, Chemical Injection -  
Surface Manifold / Filter Assembly

### PRODUCT DESCRIPTION

BlueFin's surface connection manifold can hold up to 5,000 psi. The manifold is equipped with an Anti-Siphon Valve (check valve) to eliminate the possibility of fluid being drawn down into the cap string. All components are made from 316SS. The fluid filter element is cleanable resulting in a longer usable lifespan. Assembly configuration can be modified to meet specific customer requirements.

### BENEFITS & APPLICATIONS

- Cleanable and replaceable element
- Adjustable backpressure
- Anti-siphon
- Assembly configurations vary depending on customer requirements
- Made in the USA



### GENERAL SPECIFICATIONS

Construction	All 316SS
Filter	100 Mesh or 25 Micron Standard
Max Allowable Operating Pressure	5,000 psig

### ASSEMBLY SPECS

ASV-1000 Anti-Siphon Valve or D&D Check Valve Assembly - 5,000 psi 316SS

2.5" 0-5,000 psi, Liquid-Filled Gauge Brass/SS

10,000 psi Needle Valve 316SS

### FILTRATION SPECS

HPF-3000 High Pressure Filter - 5,000 psi 316SS

**BlueFin**  
A GATE Energy Company

© 2021 BlueFin. All rights reserved. Sales of BlueFin products and services will be in accord solely with the terms and conditions contained in the contract between BlueFin and the customer.

[www.bluefin.energy](http://www.bluefin.energy)